



Project \_\_\_\_\_  
 Item No. \_\_\_\_\_  
 Model No. \_\_\_\_\_  
 Quantity \_\_\_\_\_

CSI No. 114000

# COUNTER HEIGHT FREEZER - THREE SECTION

## STANDARD FEATURES:

### Construction/Cabinet

- Exterior front and sides – heavy gauge stainless steel
- Exterior back and bottom – heavy gauge galvanized
- Stainless steel compressor housing
- Stainless steel front, door, end mount, and interior
- Heavy-duty 6" adjustable stainless steel legs
- Cabinet body is foamed-in-place minimum 2-1/2" polyurethane insulation
- Fully coved interior with welded radius corners for easy cleaning
- Optional drawers hold two 12" x 20" pans or fractional pans (pans by others)
- Rugged drawer construction
- Welded stainless steel door handle or drawer pull
- Compressor housing located on left side (optional on right side)
- Stainless steel shelf clips and shelf standards
- One adjustable chrome plated wire shelf per section

### Doors

- Self-closing door hinges with stay-open feature at 120°
- Standard left door hinged left, center and right door hinged right (other configurations available)
- Energy saving condensate heater around door opening
- Snap-in magnetic door gasket
- Impact-resistant PVC breaker strip

### Refrigeration Package

- Slideout condensing unit - enables fast and easy service
- Expansion valve refrigeration system for superior recovery and temperature pulldown
- Low pressure control – prevents compressor burnout in case of refrigerant loss
- R-449a, low GWP refrigerant for superior temperature recovery and pulldown
- Hot gas condensate evaporator quickly dissipates condensation using zero additional energy
- Receiver tank and service valves – allows reuse of refrigerant and enables rapid pulldown during times of peak demand
- Integrated sight glass – allows technicians to easily detect leaks or moisture without tools

### Control Systems & Warranty Coverage

- Digital temperature control – easily adjust setpoint between -5 to 5°F
- Master power switch
- One 9 foot electrical cord
- Warranty: 5 year compressor, 5 year parts, 1 year labor

### OPTIONS & ACCESSORIES:

- Stainless steel top (specify flat or marine edge type)
- Stainless steel back \_\_\_ bottom \_\_\_ (specify either or both)
- Additional chrome wire shelves (specify quantity) \_\_\_\_\_
- Stainless steel wire shelves in lieu of chrome shelves
- Tray slides (specify quantity)  
     "L" Type \_\_\_ Universal slides \_\_\_ "R" Type \_\_\_
- Digital temperature control & solenoid for remote models
- Refrigerant options for remote models-please specify refrigerant type
- Stainless steel curb base (specify 4" or 6" high)
- Temperature alarm
- 6" front locking casters in lieu of legs (no charge)
- 6" seismic legs
- 5" front locking casters
- 4" front locking casters
- 2 drawers in lieu of door (std depth only)
- Correctional facilities package
- Water-cooled condensing unit
- Interior LED lighting
- Marine secure latch
- ADA Height – stainless steel sub top changes overall height to 31.5" (requires 4" high casters)



CHF-75-3S-D-EM  
 93" Overall Width, Three Doors  
 (shown with optional stainless steel flat top)

## MODEL GUIDE

Model Number	Description
<input type="checkbox"/> CHF-75-3S-D-EM	93" Overall Width, Three Doors
<input type="checkbox"/> CHF-90-3S-D-EM	108" Overall Width, Three Doors
Options	Model Number Modification
<input type="checkbox"/> Remote Refrigeration	Delete suffix "EM" from model number
<input type="checkbox"/> Pass-Thru	Add prefix "PT" to model number
<input type="checkbox"/> Narrow Depth	Change "D" to "N"

## AGENCY APPROVALS:




Intertek



Intertek



# COUNTER HEIGHT FREEZER - THREE SECTION



PRODUCT DATA	CHF-75 Standard Depth	CHF-75 Narrow Depth	CHF-90 Standard Depth	CHF-90 Narrow Depth
<b>KEY DIMENSIONS</b>				
Width, Self-Contained (overall)	93.0"	93.0"	108.0"	108.0"
Width, Remote (overall)	75.0"	75.0"	90.0"	90.0"
Depth (overall)	34.5"	28.0"	34.5"	28.0"
Depth Pass-Thru Models (overall)	36.5"	30.0"	36.5"	30.0"
Height (overall inc. legs; w/ subtop)	33.5"	33.5"	33.5"	33.5"
Height (overall inc. legs; w/ optional s/s finished top)	34.5"	34.5"	34.5"	34.5"
<b>CAPACITY</b>				
Capacity (cu.ft.)	25	19	30	23
<b>ELECTRICAL</b>				
Voltage (dedicated circuit required)	115	115	115	115
Amperage (self-contained)	9.1	9.1	9.4	9.4
Amperage (remote refrigeration)	9.0	9.0	10.2	10.2
BTU requirement*, remote	2469	2330	2717	2578
NEMA Plug Configuration (self-contained only)	5-15P	5-15P	5-15P	5-15P
Horsepower (self-contained)	1/2	1/2	1/2	1/2
<b>SHIPPING</b>				
Ship Weight, Self-Contained (lbs.)	770	720	895	845
Ship Weight, Remote (lbs.)	640	590	765	705
Ship Volume, Self-Contained (cu. ft.)	107	94	124	108
Ship Volume, Remote (cu. ft.)	88	77	104	91
Crated Dimensions, Self-Contained (39" H)	99" W x 48" D	99" W x 42" D	114" W x 48" D	114" W x 42" D
Crated Dimensions, Remote (39" H)	81" W x 48" D	81" W x 42" D	96" W x 48" D	96" W x 42" D

\*90°F ambient, -15°F evaporator, 20' max. line length.

Data is for standard models: options may change specifications.

## UTILITY REFRIGERATOR

12160 Sherman Way • North Hollywood, CA 91605

Telephone: (818) 764-6200 • Fax: (818) 764-6211

[www.utilityrefrigerator.com](http://www.utilityrefrigerator.com)

*DUE TO CONTINUOUS PRODUCT IMPROVEMENTS, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.*

©/™/® Utility Refrigerator



WARNING - This product can expose you to chemicals including Di(2-ethylhexyl)phthalate (DEHP), which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

UR-CHF3 | MU